



1





2

















3

● Sternal | ● Dorsal



HS CODE
63079098
CARTON SIZE / PCS.
60 X 40 X 24 cm /12
AET (EU) N°2777/10362-04/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16083-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 10 110 00
SIZES	TU
 KG	MAX. 140 KG (VG 11.062 – Rev. 6 - 07/2018)
CE	EN 361:2002, ISO 9150, ISO 15025
Attachment	Dorsal (A), Sternal (A)
	2 / 3
MAT.  / 	
MAT.  45 mm	Aramid
 /  / 	0 / 0 / 0
	1.79 KG

 KG		MAT.  / 
Taille Poids maxi utilisateur Size Max. user weight Tamaño Peso máximo del usuario Dimensione Peso massimo dell'utente Größe Höchstgewicht des Benutzers	Nombre de boucles de réglage / boucles automatiques Number of adjustment buckles / automatic buckles Cantidad de hebillas de ajuste / hebillas automáticas Numero di fibbie di regolazione / fibbie autobloccanti Anzahl der Einstellschnallen / Schnellverschluss-Schnallen	Matière dés / boucles Material of rings / buckles Material de anillas en D / hebillas Materia del D / Fibbie Material D-Ringe/Schnallen

 /  / 
Nombre de dés porte-outils / poignées porte-matériel / triangles porte-accessoires Number of tool-holding D-rings/equipment-holding handles/accessory-holding triangles Cantidad de anillas en D portaherramientas / asas portamateriales / triángulos portaccessorios Numero di portautensili / maniglie portamateriale / triangoli portaccessori Anzahl der Werkzeug-D-Ringe / Werkzeug-Halteringe / Zubehör-Triangel



Sangle pouvant résister jusqu'à des températures maximales de 371°C
Strap that can withstand temperatures up to 371 °C
Correa que puede resistir temperaturas máximas de hasta 371 °C
Cinghie possono resistere alle temperature di massimo 371°C
Gurt hitzeresistent bis maximal 371°C



Sangle pouvant résister à des projections de métal en fusion
Strap that can withstand splashes of molten metal
Correa que puede resistir proyecciones de metal en fusión
Cinghie possono resistere alle proiezioni di metallo in fusione
Gurt beständig gegen Spritzer von Schmelzmetall