







# NiRO-S




<b>HS CODE</b>
84798997
<b>CARTON SIZE / PCS.</b>
FA 20 102 10A : 80 x 40 x 24 cm / 10 FA 20 102 15A : 80 x 40 x 24 cm / 5 FA 20 102 20A : 80 x 40 x 24 cm / 5 FA 20 102 30A : 80 x 40 x 24 cm / 5 FA 20 102 40A : 80 x 40 x 24 cm / 3 FA 20 102 50A : 80 x 40 x 24 cm / 3
<b>AET N° (in progress)</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>Technical Report SPC0314094/2122</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom
<b>MODULE D FI14/14003.01</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland


REF.	FA 20 102 10A	FA 20 102 15A	FA 20 102 20A	FA 20 102 30A	FA 20 102 40A	FA 20 102 50A
LG.	10 m	15 m	20 m	30 m	40 m	50 m
 KG	MAX. 140 KG					
CE	EN 353-2:2002					
MAT.	 INOX / PES Ø 12 mm					
	NO					
						
R(kN)	15 kN					
	1.88 kg	2.68 kg	3.03 kg	4.03 kg	4.83 kg	5.78 kg



**Longueur** Poids maxi utilisateur  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Coulisseau doté d'un point fixe**  
 Rope grab with a fixed point lock  
**Corredera provista de punto fijo**  
 Guida a punto fisso  
 Gleitelement mit Festpunkt



**Matière connecteur**  
 Material of connector  
**Material conector**  
 Materiale connettore  
**Material des Verbinders**