








REF.	FA 40 400 15
CE	EN 354:2010, ISO 9150:1988, ISO 15025:2002
LG.	1.5 m
MAT.	 45 mm ARAMID
	
R (kN)	22 kN
	1.48 KG

MAT.		R (kN)
Matière	Matière connecteurs	Résistance (en kN)
Material	Material of connectors	Resistance (kN)
Material	Material de los conectores	Resistencia (en kN)
Materia	Materie connettori	Resistenza (in kN)
Material	Material der Verbinder	Belastbarkeit (in kN)



**Sangle pouvant résister jusqu'à des températures maximales de 371°C**

Strap that can withstand temperatures up to 371 °C

**Correa que puede resistir temperaturas máximas de hasta 371 °C**

Cinghie possono resistere alle temperature di massimo 371°C

Gurt hitzeresistent bis maximal 371°C




**Sangle pouvant résister à des projections de métal en fusion**

Strap that can withstand splashes of molten metal

**Correa que puede resistir proyecciones de metal en fusión**

Cinghie possono resistere alle proiezioni di metallo in fusione

Gurt beständig gegen Spritzer von Schmelzmetall



<b>HS CODE</b>
63079098
<b>CARTON SIZE / PCS.</b>
60 x 40 x 24 cm / 12
<b>AET (UE) N°2777/10811-02/E01-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>AET (UKCA) N°AB0321/16031-01/E01-01</b>
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>MODULE D 11 IN14/14003</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom